This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS

- TEXT CUT OFF AT TOP, BOTTOM OR SIDES

- FADED TEXT

- ILLEGIBLE TEXT

- SKEWED/SLANTED IMAGES

- COLORED PHOTOS

- BLACK OR VERY BLACK AND WHITE DARK PHOTOS

- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images, please do not report the images to the Image Problem Mailbox.

The Patent Office

I800 / 229

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

REC'D **0 3 MAY 2000**

WIPO   PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated   05 April 2000

PRIORITY
DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

An Executive Agency of the Department of Trade and Industry

ents Form 1/77   THE PATENT OFFICE   **The**
                 A   **Patent**
Patents Act 1977   24 FEB 1999   **Office**
(Rule 16)
                 RECEIVED BY FAX

24FE⬤ E427822-1 D02716
F01/3700 0/00 - 9904181.6

Request for grant of a patent

*(See the notes on the back of this form. You can also get
an explanatory leaflet from the Patent Office to help
you fill in this form)*

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference	PAT 99409 GB
2. Patent application number *(The Patent Office will fill in this part)*	**9904181.6** 24 FEB 1999
3. Full name, address and postcode of the or of each applicant *(underline all surnames)*	NOKIA MOBILE PHONES LIMITED KEILALAHDENTIE 4 02150 ESPOO FINLAND
Patents ADP number *(if you know it)*	
If the applicant is a corporate body, give the country/state of its incorporation	FINLAND *5911995004*
4. Title of the invention	TELECOMMUNICATION SERVICES IDENTIFICATION
5. Name of your agent *(if you have one)* "Address for service" in the United Kingdom to which all correspondence should be sent *(including the postcode)*	NOKIA IPR DEPARTMENT NOKIA HOUSE SUMMIT AVENUE FARNBOROUGH HAMPSHIRE GU140NG UK 7577638001
Patents ADP number *(if you know it)*	

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and *(if you know it)* the or each application number	Country	Priority application number *(if you know it)*	Date of filing *(day / month / year)*
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application		Date of filing *(day / month / year)*

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? *(Answer 'Yes' if:* *a) any applicant named in part 3 is not an inventor, or* *b) there is an inventor who is not named as an applicant, or* *c) any named applicant is a corporate body.* *See note (d))*	Yes

Patents Form 1/77

Patents Form 1/77

9. Enter the number of sheets for any of the
    following items you are filing with this form.
    Do not count copies of the same document

Continuation sheets of this form

Description   22

Claim(s)   4

Abstract   1

Drawing(s)   7

---

10. If you are also filing any of the following,
    state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right
to grant of a patent *(Patents Form 7/77)*

Request for preliminary examination
and search *(Patents Form 9/77)*   1

Request for substantive examination
(Patents Form 10/77)

Any other documents
(please specify)

---

11.   I/We request the grant of a patent on the basis of this application.

                                       Signature   Date
                                       JULIET J G HIBBERT   24.2.1999

---

12. Name and daytime telephone number of
    person to contact in the United Kingdom   Kiss K Jeffery 01252 365306

Warning

*After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication
or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You
will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the
United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting
written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the
United Kingdom for a patent for the same invention and either no direction prohibiting publication or
communication has been given, or any such direction has been revoked.*

Notes

a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.

b) Write your answers in capital letters using black ink or you may type them.

*c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate
    sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be
    attached to this form.*

d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.

e) Once you have filled in the form you must remember to sign and date it.

f) For details of the fee and ways to pay please contact the Patent Office.

Patents Form 1/77

1 .

Telecommunication Services Identification

The present invention relates to a method and apparatus for identifying the type of telecommunications service required during call establishment over two networks. In particular, it relates to a method and apparatus for establishing call control appropriate to the telecommunications service identified by the originating network.

Traditionally, different telecommunication services have been identified by adopting a multiple numbering scheme. That is, by dedicating a specific subscriber number to a specific service. For example, in GSM, the subscriber may currently have assigned mobile terminated GSM speech, data and/or fax numbers depending upon his profile. In the future, it is proposed that he will also have the option of further high speed data and multimedia services which, too, will have dedicated subscriber numbers.

Figure 1 of the accompanying drawings illustrates the GSM public land mobile network (PLMN) and Figure 2 illustrates the call control between the public switched telephone network (PSTN) and this PLMN using the aforementioned multiple numbering scheme.

As can be seen from Figure 1, the GSM architecture comprises a gateway mobile switching centre (MSC) 10 which interfaces with fixed networks such as the PSTN 15 and a GSM radio network. The GSM radio network comprises base station systems comprising a base station controller 16 and base transceiver stations (BTS) 17. Mobile stations are coupled to the BTSs via an air interface. The gateway MSC is also connected to subscriber and terminal equipment databases in the form of a home location register (HLR) 12, visitor location register (VLR) 13, and equipment identity register (EIR) 14. The EIR contains information relating to the mobile terminals and the VLR provides a local store of all the information required to handle calls to and from mobile users in the location area relating to that particular VLR. The HLR 12 permanently stores all the user parameters of the mobile stations,

2

including the subscriber numbers associated with a particular mobil station and th ir corresponding service typ . Since the PSTN is an analogue network and the GSM PLMN is digital, they are not directly compatible. Hence, the gateway MSC 10 has an associated interwo:king function (IWF) 11, which is a functional entity enabling interworking betv/een the PLMN and PSTN. Shown separately from the IWF 11 in Figure 1, is the MSCs transcoder TC 101. This TC converts analogue speech into corresponding digital signals.

As illustrated in Figure 2, when a call originates from the PSTN 15 (in this example a data call), an initial SETUP message is sent which includes the called line identification (CLI) [Step 1]. The HLR contains a database entry corresponding to this CLI indicating the call type. The MSC 10 asks the HLR 12 for this call type (bearer capability) corresponding to the CLI, and sends a setup message to the MS 18 to inform it of the incoming call and of the call type [Step 2]. The MS 18 responds by sending a CALL-PROC message after having checked the compatibility (e.g. user profile capability) with the requested bearer capability [Step 3]. This message is forwarded to the PSTN by the MSC 10 [Step 4]. Then, the MS sends an ALERT message to the MSC informing it that ringing has started to the called subscriber [Step 5] and consequently the MSC connects the ringing tone to the calling subscriber [Step 6]. Finally, a CONNECT message is sent from the MS to the MSC [Step 7] and then from the MSC to the PSTN [Step 8] when the called subscriber answers and a connection appropriate for the data call is made.

According to one aspect of the present invention, there is provided a switch for establishing a call between a terminal of an originating analogue network and a terminal of a digital terminating network, the switch comprising: an input for receiving call type information in a first format from the originating network; means for reformatting received call type information into a second format; an output means for outputting the call type information in the second format over the terminating network; and connection means for completing a connection, suitable for the identified call type, between the terminals.

3

This switch enables the elimination and/or reduction of the use of the aforementioned multinumbering sch m .

The call type information may relate to teleservice and/or bearer information. The provision of bearer information enables the terminating network to use the same bitrate as is available on the originating side, thereby ensuring that bandwidth efficiency is optimised.

The terminating network is preferably a wireless communications network, such as an UMTS or GSM network.

Optionally the switch is an MSC or GMSC.

The switch may further comprise means, coupled to the input, for determining primary call type information on the basis of a subscriber number, for forwarding first primary call type information to the output, and for forwarding further primary call type information to the reformatting means. Such a switch may, for example, enable a dual numbering system to be adopted, to distinguish between calls of primary types "speech" and "data". In this case, all calls of "speech" primary type are preferably automatically connected, and further determination of actual data type is made of calls of "data" primary type.

According to another aspect of the present invention, there is provided method for establishing a call between a terminal of an originating analogue network and a terminal of a digital terminating network, the method comprising: receiving call type information in a first format from the originating network; reformatting received call type information into a second format; outputting the call type information in the second format over the terminating network; and completing a connection, suitable for the identified call type, between the terminals.

4

According to a further aspect of the present invention, th re is provided a method for establishing a call between a terminal of an originating analogue network and a terminal of a digital terminating network, the method comprising: establishing a call of a predetermined type; transmitting call type information in a first format from the originating terminal to the terminating network; reformatting received call type information into a second format; transmitting the call type information in the second format to the terminating terminal; and establishing a connection, suitable for the identified call type, between the terminals.

According to another aspect of the invention, there is provided a switching system for establishing a call from a terminal of an originating analogue network and a terminal of a digital terminating network, the switching system comprising: means for receiving call type information in a first format from the originating network; means for reformatting received call type information into a second format; means for transmitting the call type information in the second format over the terminating network; and connection means for completing a connection, suitable for the identified call type, between the terminals.

Embodiments of the present invention will now be described, by way of example, with reference to the accompanying drawings, of which:

Figure 1 illustrates the current GSM PLMN and its connection to the PSTN;
Figure 2 illustrates data call establishment from a PSTN terminal to a mobile station using the conventional multiple numbering plan;
Figure 3 illustrates identification of the telecommunications service required for a PSTN originating call by an MSC of the present invention;
Figure 4 illustrates call establishment from a PSTN terminal to a mobile station using a single numbering plan according to an embodiment of the present invention;

5

Figures 5a and b illustrate. call establishment from a ᴾSTN terminal to a mobile station using a bi-numbering plan according to another embodiment of the present invention; and

Figure 6 illustrates typical mapping information for an H.3ᴣ4 call.

The invention concerns a method and apparatus for thei control of different call types between incompatible networks, using unique call type differentiation. It is described with reference to the netwcrks shown in Figure 1, namely the analogue PSTN network which uses in bard signalling and the wireless digital GSM network which uses out band signalling. However, the invention is not restricted to call control over these networks, and is equally applicable to other non directly compatible networks. One area in which the invention is proposed for use in the future is between an analogue network (such as the PSTN) and universal mobile telecommunication system (UMTS).

As is illustrated in Figure 1, a conventional MSC 10 of the GSM network comprises an interworking function (IWF) 11 which interfaces with the PSTN. In this embodiment of the present invention, the MSC differs in that it has additional functionality, as outlined in Figure 3. Generally, this functionality is provided by the IWF. (However, alternatively, it may be provided by other parts of the MSC and/or other switches in the network).

Firstly the IWF of this embodiment detects signalling from the PSTN [Step 301]. Then it interprets the in band signalling messages relating to the telecommunication services and maps these messages into appropriate digital out band signalling [Step 302]. Typical mapping information for an H.324 call is shown in Figure 6, and further information on the mapping process is provided under the heading "Mapping" below.

Telecommunication services can be divided into two main types: teleservices and bearer services. Teleservices provide the full capacity for communications by means of terminal and network functions, and comprise and high layer attributes (OSI layers 1-7), whereas bearer services, in

6

contrast, provide the capability of transmission of signals between the PSTN and PLMN access points and only involve the lower lay r functions (OSI layers 1-3). The mapping of the teleservices eliminates the need for the aforementioned multinumbering scheme. It thus simplifies operability of the system from a user standpoint, as the caller only needs to remember one number for the party to be called. Also, it reduces the need to increase the length of subscriber numbers to cater for additional services subscribed to in the future. Furthermore, the processing strain on the HLR 12 is reduced. Mapping the bearer service, on the other hand, provides the additional advantage of enabling the radio bearer to be optimised That is, the radio bearer may be negotiated to match that of the PSTN, thus optimising the bandwidth used by the wireless network. After mapping, the MSC 10 provides the appropriate call set up messaging for the identified service type [Step 303]. Consequently, the mobile station 18 is informed of the service type and the appropriate call connection is effected.

Figure 4 illustrates call establishment from a PSTN terminal to a mobile station using a single numbering plan according to a preferred embodiment of the present invention. In this embodiment, the MSC 10 is adapted to conform at least with V.8, and preferably V8bis, so that it can recognise a call type from the V.8/V8bis call function information category. In particular, the MSC's modem pool includes a modem, which conforms to V.34, so as to support V8 and optionally V8bis. This modem acts as a signalling detector 41 for detecting and interpreting V8/V8bis signalling.

When a call originates from the PSTN 15 (in this example a multimedia call), an initial SETUP message is sent from the PSTN terminal to the MSC 10 [Step 1]. The MSC 10, in turn, sends a SETUP message to the MS 18 associated with the subscriber number dialled using GSM/UMTS call control signalling [Step 2]. The SETUP message informs the MS 18 of the incoming call and of a default call type: in this case speech. The MS 18 responds by sending a CALL-PROC message after having checked the compatibility with the requested bearer capability [Step 3]. This message is forwarded to the

7 ·

PSTN by the MSC 10 [Step 4]. Then, the MS sends an ALERT m ssage to the MSC informing it that ringing has started to the call cl subscriber [St p 5] and consequently the MSC connects the ringing tone to the calling subscriber [Step 6]. Finally, a CONNECT message is sent from the MS to the MSC [Step 7] and then from the MSC to the PSTN [Step 8] when the called subscriber answers and a default speech connection is made [Step 9].

Upon connection, the V.8/V.8bis signalling detector 41 of the MSC 10 interprets the PSTN originated V.8/V.8bis signalling [Step 10]. The signalling related to the telecommunication services is mapped into corresponding GSM/UMTS signalling by the MSC 10 and, in this embodiment, the MSC instigates modification of the bearer using the GSM layer 3 call control protocol (GSM 04.08). In other words, in this case the s.gnalling detector 41 identifies the telecommunication service categories as a multimedia teleservice category (H.324) and a 28.8kbps transparent bearer service category. In other cases more than one bearer services may be selected: for example, one for images and one for data. If necessary, connections within the MSC (including activation of modems) are rearranged for example as in the GSM Phase 1 proposed "alternate speech and data" service. The GSM/UMTS speech bearer output to the mobile station speech channel is preferably blocked to prevent loudspeaker activation in the MS until the call type has been determined. However connection between the terminals is maintained.

Next, the bearer capability for the wireless network is set to be the same as that determined for the PSTN, so as to optimise the bandwidth, and the MS 18 is informed of the requested call type [Step 11]. The MS returns a message to the MSC to complete the GSM/UMTS bearer modification process [Step 12]. The connection is now complete for multimedia communication between the PSTN terminal and MS 18 [Step 13]. Communication takes place via the MSC modem pool using the optimised radio bearer.

8

An alternative embodiment of the invention enabling the use of a r duc d numbering plan will now be described. Figures 5a and 5b illustrate call establishment from a PSTN terminal to a mobile station using a dual numbering plan. This embodiment provides a hybrid arrangement in which only two numbers are used: one to identify speech calls and the other to identify data calls. As in the arrangement of Figure 2, the HLR 12 contains a database entry corresponding to the called line identification indicating the call type. However, in this embodiment, this database has only two entries: one indicating that the call type is speech and the other indicating that the call type is data. If the call type is speech, the PSTN originating signal is transcoded by the TC 101 of the MSC 10 and transmitted over the radio network. However, if it is data, the actual type is determined by the IWF 11 as described with reference to Figure 3 above.

Call establishment in this embodiment will now be described in more detail, with reference to Figures 5a and b.

Figure 5a illustrates call establishment for a speech call. When a call originates from the PSTN 15, an initial SETUP message is sent which includes the called line identification (CLI) – in this case for a speech call. [Step 1]. As mentioned above, the HLR contains a database entry corresponding to this CLI indicating the call type as speech. The MSC 10 asks the HLR 12 for this call type (bearer capability) corresponding to the CLI, and sends a setup message to the MS 18 to inform it of the incoming call and that the call type is speech [Step 2]. The MS 18 responds by sending a CALL-PROC message after having checked the compatibility (e.g. user profile capability) with the requested bearer capability [Step 3]. This message is forwarded to the PSTN by the MSC 10 [Step 4]. Then, the MS sends an ALERT message to the MSC informing it that ringing has started to the called subscriber [Step 5] and consequently the MSC connects the ringing tone to the calling subscriber [Step 6]. Finally, a CONNECT message is sent from the MS to the MSC [Step 7] and then from the MSC to the PSTN [Step 8]

9

when the called subscriber answers and a connection appropriate for th speech call is made.

Figure 5b illustrates call establishment for a data call. When a call originates from the PSTN 15 (in this example a multimedia call), an initial SETUP message is sent which includes the called line identification (CLI) – in this case for a data call. [Step 1]. As mentioned above, the HLR contains a database entry corresponding to this CLI indicating the call type as data. The MSC 10 asks the HLR 12 for this call type (bearer capability) corresponding to the CLI, and sends a setup message to the MS 18 to inform it of the incoming call and of a default call type (e.g. a default data type) [Step 2]. The MS 18 responds by sending a CALL-PROC message after having checked the compatibility with the requested bearer capability [Step 3]. This message is forwarded to the PSTN by the MSC 10 [Step 4]. Then, the MS sends an ALERT message to the MSC informing it that ringing has started to the called subscriber [Step 5] and consequently the MSC connects the ringing tone to the calling subscriber [Step 6]. Finally, a CONNECT message is sent from the MS to the MSC [Step 7] and then from the MSC to the PSTN [Step 8] when the called subscriber answers and the default connection is made [Step 9].

Next, the MSC endeavours to determine the actual data type. In this example, upon connection, the V.8/V.8bis signalling detector 41 of the MSC 10 interprets the PSTN originated V.8/V.8bis signalling [Step 10]. The signalling related to the telecommunication services is mapped into corresponding GSM/UMTS signalling by the MSC 10 and, in this embodiment, the MSC instigates modification of the bearer using the GSM layer 3 call control protocol (GSM 04.08). In other words, in this case the detector 41 identifies the telecommunication service categories as a multimedia teleservice category (H.324) and a 28.8kbps transparent bearer service category. If necessary, connections within the MSC (including activation of modems) are rearranged for example as in the GSM Phase 1 proposed "alternate speech and data" service. The GSM/UMTS speech bearer output

10

to the mobile station speech channel is preferably blocked to prevent loudspeak r activation in the MS until the call type has been d termined. However connection between the terminals is maintained.

Next, the bearer capability for the wireless network is set to be the same as that determined for the PSTN, so as to optimise the bandwidth, and the MS 18 is informed of the requested call type [Step 11]. The MS returns a message to the MSC to complete the GSM/UMTS bearer modification process [Step 12]. The connection is now complete for multimedia communication between the PSTN terminal and MS 18 [Step 13]. Communication takes place via the MSC modem pool using the optimised radio bearer.

Mapping

Typical mapping by the MSC will now be described, firstly from V.8 to GSM and then optional mapping for V.8bis. As will be appreciated, this mapping is only exemplary and similar mapping could take place for future networks such as UMTS. GSM signalling is generally derived from ISDN, i.e. it is based on ITU-T Q.931 recommendation. So too are 3G telecommunication systems such as UMTS, hence, their particular compatibility with such mapping methods.

In this embodiment, information relating to the teleservice is mapped into the HLC (high level capability) information element in GSM (based on Q.931). Similarly, information relating to the bearer service is mapped into the BC (bearer capability) information element in GSM. Further details of the HLC, BC and also the LLC (low level capability element) are also provided in the following description of the mapping.

The V.8, V.8bis and GSM signalling information, which is relevant to the determination of telecommunication service types, is outlined below. The

11.

references refer to the following documents, the contents of which are incorporated herein by reference:

[1]   ITU-T Recommendation F.721 (08/92) - Videotelephony teleservice for ISDN

[2]   ITU-T Recommendation F.700 (07/96) - Framework Recommendation for audiovisual/multimedia services

[3]   ITU-T Recommendation V.8 (02/98) - Procedures for starting sessions of data transmission over the public switched telephone network

[4]   ITU-T Recommendation V.8bis (08/96) - Procedures for the identification and selection of common modes of operation between data circuit-terminating equipments (DCEs) and between data terminal equipments (DTEs) over the general switched telephone network and on leased point-to-point telephone-type circuits

[5]   ITU-T Recommendation H.324 (2/98) - Terminal for low bit rate multimedia communication

[6]   Digital cellular telecommunications system (Phase 2+); Mobile radio interface layer 3 specification, GSM 04.08 version 6.2.0 Release 1997

[7]   ITU-T Recommendation H.245 (2/98) - Control protocol for multimedia communication.

V.8 signalling to be mapped [3]

12

Table 2 in [3] lists the information categories that are availabl in V.8
signalling. As can be seen, the call-function octet has 3 option bits, and Table
3 in [3] illustrates how these option bits are used to identify particular call
functions. As mentioned above, the information interpreted from the call
function category can be mapped into the Q.931 HLC information element to
provide the GSM network with information pertaining to the teleservice or call
function and the bearer service.

Table 4 in [3] indicates the availability of PSTN V-Series modulation modes
other than V.90. The availability is only shown if the modulation mode can be
used with the indicated call function, and if it is desired to convey that
capability to the remote DCE. For example, if an H.324 application is used,
the use of a V.34 full duplex mode is mandatory, and the other options would
not be indicated. The modulation mode information is only used between
DCEs in order to find out the common modulation modes. After selection of a
common modulation mode (e.g. V.34), the MSC/IWF determines the data rate
from the modem (e.g. 28.8kbps) on the basis of how good the quality (BER)
of the PSTN line is.

GSM (Q931 based) signalling onto which the above V8 signalling is mapped
by the MSC

GSM specification 04-08 [6] defines the messages for circuit switched call
control. In particular, section 9.3.23.1 in [6] defines the SET UP message
content for mobile terminated call establishment. This message is sent over
the network to the mobile station to initiate mobile terminated call
establishment. The SET UP message contains relevant information elements
for the BC (bearer capability), HLC (high level capability) and LLC (low level
capability). As mentioned above, it is these information elements which the
V8 call function category information is mapped into. (In GSM at least, not all
of these information elements are compulsory. However, in UMTS, at least
the BC and HLC should be.)

13

BC

The purpose of the bearer capability information element is to describe the bearer service to be used in the connection. Figure 10.5.88 in [6] illustrates the BC element for GSM. This element contains 16 octets (8 bit units). Certain bits or coding points need to be stored in octets 3, 4, 6, 6a, 6c and 6d in order to support H.324, as outlined below.

Transfer mode (octet 3):
Bit
4
0   **circuit mode**
1   packet mode

- Circuit mode is selected

Duplex mode (octet 4)
Bit
4
0   half duplex
1   **full duplex**

- Full duplex is selected

Synchronous/asynchronous (octet 6)
Bit
1
0   **synchronous**
1   asynchronous

- Synchronous is selected

14

User rat   (octet 6a)

Bits

4 3 2 1

0 0 0 1   0.3 kbit/s Recommendation X.1 and V.110

0 0 1 0   1.2 kbit/s Recommendation X.1 and V.110

0 0 1 1   2.4 kbit/s Recommendation X.1 and V.110

0 1 0 0   4.8 kbit/s Recommendation X.1 and V.110

0 1 0 1   9.6 kbit/s Recommendation X.1 and V.110

0 1 1 0   12.0 kbit/s transparent (non compliance with X.1 and V.110)

0 1 1 1   1.2 kbit/s/75 bit/s Recommendation V.23, (asymmetric) X.1,
V.110.

The coding points shown above are used to indicate the user rate. At present
there is no e.g. 28.8 kbps user rate available in GSM. However, Q:931 offers
a wider set of user data rates that can be used when specifying the BC
information element. (An outline of how the mapping might occur for the
28.8kbps and other unspecified data rates in GSM is outlined under the
heading "Potential BC for other user rates".

Connection element (octet 6c)

Bit

7 6

0 0   transparent

0 1   non transparent (RLP)

1 0   both, transparent preferred

1 1   both, non transparent preferred

• Transparent is selected

Other modem type (octet 6d)

Bits

15

7 6

0 0   no other modem type specified in this field

0 1   V.32bis

1 0   V.34

      • V.34 is selected

Potential BC for other bit user rates.

Fixed network user rate (octet 6d)

Bit

5 4 3 2 1

0 0 0 0 0   Fixed network user rate not applicable/No meaning is
           associated with this value.

0 0 0 0 1   9.6 kbit/s Recommendation X.1 and V.110

0 0 0 1 0   14.4 kbit/s Recommendation X.1 and V.110

0 0 0 1 1   19.2 kbit/s Recommendation X.1 and V.110

0 0 1 0 0   28.8 kbit/s Recommendation X.1 and V.110

0 0 1 0 1   38.4 kbit/s Recommendation X.1 and V.110

0 0 1 1 0   48.0 kbit/s Recommendation X.1 and V.110(synch)

0 0 1 1 1   56.0 kbit/s Recommendation X.1 and V.110(synch) /bit
           transparent

0 1 0 0 0   64.0 kbit/s bit transparent

For an example data rate of 28.8 kbps, the element highlighted above might
be used. So 28.8 is selected.

Acceptable channel codings (octet 6e), mobile station to network direction:

Bit

7

0   TCH/F14.4 not acceptable

1   TCH/F14.4 acceptable

If 14.4 is implemented then it can be selected.

16

Bit

6

0   Spare

Bit

5

0   TCH/F9.6 not acceptable

1   **TCH/F9.6 acceptable**

Normally, 9.6 is implemented as well

Bit

4

0   TCH/F4.8 not acceptable

1   **TCH/F4.8 acceptable**

4.8 exists even though not widely used

Acceptable channel codings (octet 6e), network to MS direction:

Bits 4 to 7 are spare and shall be set to "0".

This would mean that network can not decide what kind of channel coding is used. This is required in the present case since networks initiate the call setup renegotiation. A change to current GSM implementation is needed to effect this.

Maximum number of traffic channels (octet 6e), MS to network direction:

Bits

3 2 1

0 0 0   1 TCH

0 0 1   2 TCH

0 1 0   3 TCH

0 1 1   4 TCH

1 0 0   5 TCH

1 0 1   6 TCH

17

1 1 0   7 TCH

1 1 1   8 TCH

28.8kbps can be obtained by combining two 14.4 channels using HSCSD.
This could also be done by combining three 9.6 channels.

Maximum number of traffic channels (octet 6e), network to MS direction:
Bits 1 to 3 are spare and shall be set to "0".
As above, this would mean that network is unable to decide what kind of
channel coding is used, and would require a modification to GSM.

LLC

The low layer compatibility information element is illustrated in Figure10.5.104
of [6]. The purpose of the low layer compatibility information element is to
provide a means which should be used for compatibility checking by an
addressed entity (e.g., a remote user or an interworking unit or a high layer
function network node addressed by the calling user). The low layer
compatibility information element is transferred transparently by a PLMN
between the call originating entity (e.g. the calling user) and the addressed
entity.

Except for the information element identifier, the low layer compatibility
information element is coded as in ETS 300 102-1.

This information element is not necessarily needed because the same coding
can be conveyed in the BC.

HLC

The purpose of the high layer capability information element is to provide a
means by which the remote user can check for compatibility.

18

The high layer compatibility information element is coded as shown in figure 10.5.102 and table 10.5.125 of [6].

The high layer compatibility information element is transported transparently by a PLMN between a call originating entity (e.g. a calling user) and the addressed entity (e.g. a remote user or a high layer function network node addressed by the call originating entity). However, if explicitly requested by the user (at subscription time), a network which provides some capabilities to realise teleservices may interpret this information to provide a particular service.

The following HLC code points can be found from the Q.931 recommendation:

High layer characteristics identification (octet 4)
Bits
7 6 5 4 3 2 1
0 0 0 0 0 0 1 Telephony
0 0 0 0 1 0 0 Facsimile Group 2/3 (Recommendation F.182 [68])
0 1 0 0 0 0 1 Facsimile Group 4 Class I (Recommendation F.184 [69])
0 1 0 0 1 0 0 Teletex service, basic and mixed mode of operation
           (Recommendation F.230 [70]) and facsimile service Group 4,
           Classes II and III (Recommendation F.184)
0 1 0 1 0 0 0 Teletex service, basic and processable mode of operation
           (Recommendation F.220 [71])
0 1 1 0 0 0 1 Teletex service, basic mode of operation (Recommendation
           F.200 [72])
0 1 1 0 0 1 0 Syntax based Videotex (Recommendations F.300 [73] and
           T.102 [74])
0 1 1 0 0 1 1 International Videotex interworking via gateways or interworking
           units (Recommendations F.300 and T.101 [75])
0 1 1 0 1 0 1 Telex service (Recommendation F.60 [76])

19

0 1 1 1 0 0 0 Message Handling Systems (MHS) (X.400 - Series
               Recommendations [77])

1 0 0 0 0 0 1 OSI application (Note 2) (X.200 - Series Recommendations [78])

1 0 1 1 1 1 0 Reserved for maintenance (Note 4)

1 0 1 1 1 1 1 Reserved for management (Note 4)

1 1 0 0 0 0 0 Audio visual (Recommendation F.721 [79])

1 1 0 0 0 0 1 through 1 1 0 1 1 1 1   Reserved for audiovisual services [2]

1 1 1 1 1 1 1 Reserved

The F.700 Recommendation [2] provides a methodology for constructing
multimedia services which is timely and responsive to the needs of both the
End-User and Service Provider. This methodology links generic End-User
application requirements with the established set of network independent
building blocks or other communications capabilities being developed within
ITU-T. The procedures described in this Recommendation are intended for
use in developing a series of General Service Recommendations which
combine the required communication tasks and media components into an
architecture for generic services (e.g. for Multimedia Conferencing Service,
Multimedia Distribution Service, etc.). Where applicable Recommendations
are not yet available, this methodology can be used as the basis for a
structured dialogue between End-Users and Service Providers in arriving at a
responsive service solution.

Bits 1100001 through 1101111, specified in F.700, could be used for e.g.
H.324 code point or a totally new codepoint could be designed for UMTS use.

V.8bis signalling to be mapped [4]

Table 6-2 in [4] lists the standard information categories that are available in
V.8bis signalling. It comprises categories such as data and H.324 multimedia
terminal to readily cater for such future teleservices. The coding for these
teleservices are illustrated in Tables 6-3 and 6-5 of [4]. One advantage of the
V.8bis capability exchange is that, in most cases, it enables terminals to

20

ascertain very quickly when operation in H.324 mode is desired. This is because V.8bis capabilities indicate only the most basic and commonly used modes. If an H.324 operation mode not signalled by V.8bis is desired, the terminal must complete call establishment and perform a H.245 [7] capabilities exchange to determine if the far-end terminal supports the desired mode.

Within the Rec. V.8bis Communications Capabilities (CC) field for H.324, the CC field is formatted into one or more sub-fields. Each sub-field ends with the octet in which bit [n] is set to 1. Following the first sub-field, the remaining sub-fields, if present, shall appear in the same order in which the bits indicating their presence are transmitted. The actual bit assignments can be seen from [4].

In the first sub-field the following bits are allocated:

Name	Meaning
Video	Shall be set only if bi-directional video is supported per Rec. H.324 (sec. 6.6).
Audio	Shall be set only if bi-directional audio is supported per Rec. H.324 (sec. 6.7).
Encryption	Shall be set only if encryption is supported per Rec. H.324 (sec. 9.2).
Data	Indicates that a data subfield is present. Shall be set only if one or more bits in the data subfield are set.

Possible future allocations include Profiles (new subfield).

In the Data subfield, the following bits are allocated:

Name Meaning

21

T.120 Shall be set only if T.120 conferencing is supported per Rec. H.324
       (sec. 6.8.2.1).

T.84   Shall be set only if T.84 still image transfer is supported per Rec.
       H.324 (sec. 6.8.2.2).

T.434 Shall be set only if T.434 file transfer is supported per Rec. H.324 (sec.
       6.8.2.3).

V.42   Shall be set only if V.42 user data is supported per Rec. H.324 (sec.
       6.8.1.2/6.8.2.6).

V.14   Shall be set only if V.14 user data is supported per Rec. H.324 (sec.
       6.8.1.1/6.8.2.6).

PPP   Shall be set only if IETF Point-to-Point protocol is supported via the
       Network Layer Protocol Identifier (NLPID) per Rec. H.324 (sec.
       6.8.2.5).

T.140 Shall be set only if T.140 Text Conversation Protocol for Multimedia
       Application is supported per Rec H.324 (sec 6.8.2.8).

Other modes beside those indicated in V.8bis, such as unidirectional modes,
may be supported by terminals as signalled via H.245 capabilities exchange.

With V.8bis signalling can also be used when the call is first started in speech
mode and after that it is switched to e.g. H.324 mode. For this reason, the
MSC/IFW must all the time be able to listen the possible inband signalling
coming from PSTN modem. The switch of service then initiates the bearer
renegotiation in UMTS side where the "old" bearer is accomplished according
to QoS parameters needed to H.324 call.

The present invention includes any novel feature or combination of features
disclosed herein either explicitly or any generalisation thereof irrespective of
whether or not it relates to the claimed invention or mitigates any or all of the
problems addressed.

In view of the foregoing description it will be evident to a person skilled in the
art that various modifications may be made within the scope of the invention.

22

For xample, th reduced numbering scheme is not restriceted to only one or
two numbers for call type differentiation. It will be appreciated that the
reference to H.324 throughout this text is purely exemplary and that the
invention is also applicable to other data types.

23

Claims

1.   A switch for establishing a call between a terminal of an originating analogue network and a terminal of a digital terminating network, the switch comprising:

an input for receiving call type information in a first format from the originating network;

means for reformatting received call type information into a second format;

an output means for outputting the call type information in the second format over the terminating network; and

connection means for completing a connection, suitable for the identified call type, between the terminals.

2.   A switch as claimed in claim 1, wherein the call type information comprises teleservice information.

3.   A switch as claimed in claim 1 or 2, wherein the call type information comprises bearer service information.

4.   A switch as claimed in any preceding claim, wherein the first format is an in band format.

5.   A switch as claimed in any preceding claim, wherein the second format is an out band format.

6.   A switch as claimed in any preceding claim, wherein the terminating network is a wireless communications network.

7.   A switch as claimed in any preceding claim, wherein the terminating network is a universal mobile telecommunications system (UMTS) network.

24

8.   A switch as claimed in any of claims 1 to 6, wherein the terminating network is a GSM network.

9.   A switch as claimed in claim 8, wherein the switch is a mobile switching centre.

10.   A switch as claimed in any preceding claim, further comprising:
       means, coupled to the input, for determining primary call type information on the basis of a subscriber number, for forwarding first primary call type information to the output, and for forwarding further primary call type information to the reformatting means.

11.   A method for establishing a call between a terminal of an originating analogue network and a terminal of a digital terminating network, the method comprising:
       receiving call type information in a first format from the originating network;
       reformatting received call type information into a second format;
       outputting the call type information in the second format over the terminating network; and
       completing a connection, suitable for the identified call type, between the terminals.

12.   A method for establishing a call between a terminal of an originating analogue network and a terminal of a digital terminating network, the method comprising:
       establishing a call of a predetermined type;
       transmitting call type information in a first format from the originating terminal to the terminating network;
       reformatting received call type information into a second format;
       transmitting the call type information in the second format to the terminating terminal; and

25

establishing a connection, suitable for the identifiec call type, betwe n the terminals.

13.   A method as claimed in claim 11 or 12, further comprising:

determining primary call type information on the basis of a subscriber number;

providing a predetermined connection if the primary call type corresponds to the call type of the predetermined connecton; and

performing the reformatting, transmitting and establishing steps if the primary call type is another type.

14.   A switching system for establishing a call between a terminal of an originating analogue network and a terminal of a digital terminating network, the switching system comprising:

means for receiving call type information in a first format from the originating network;

means for reformatting received call type information into a second format;

means for transmitting the call type information in the second format over the terminating network; and

connection means for completing a connection, suitable for the identified call type, between the terminals.

15.   A switch for establishing a call between a terminal of an originating analogue network and a terminal of a digital terminating network, substantially as hereinbefore described with reference to, and/or as illustrated in any one, or any combination, of Figures 3 to 6 of the accompanying drawings.

16.   A system for establishing a call between a terminal of an originating analogue network and a terminal of a digital terminating network, substantially as hereinbefore described with reference to, and/or as illustrated in any one, or any combination, of Figures 3 to 6 of the accompanying drawings.

26

17. A meth d for establishing a call between a t rminal of an originating analogue network and a t rminal of a digital t rminating network, substantially as hereinbefore described with reference to, and/or as illustrated in any one, or any combination, of Figures 3 to 6 of the accompanying drawings.

27

ABSTRACT

Telecommunication S rvic s Identificati n

1. A method and apparatus are disclosed for identifyirig telecommunications services. The apparatus enables call establishment between a terminal of an originating analogue network and a terminal of a digital terminating network. It comprises an input for receiving call type information in a first format from the originating network, means for reformatting received call type information into a second format, output means for outputting the call type information in the second format over the terminating network; and connection means for completing an appropriate connection between the terminals.

[Figure 3]

1/7

FIGURE 1

2/7

Terminal appl.

MS 18

Terminal appl.

PSTN/C7 15

MSC 10

Multiple Numbering Plan

HLR: this CLI is a data service #!

SETUP (BC=data call)

CALL_PROC

ALERT

CONNECT

② ③ ⑤ ⑦

SETUP(CLI)

CALL PROC (BC, ...)

ALERT

CONNECT

① ④ ⑥ ⑧

CLI=special data service number

Transparent data

V.34

FIGURE 2

3/7


FIGURE 3

THIS PAGE BLANK (USPTO)

4/7

FIGURE 4

THIS PAGE BLANK (USPTO)

5/7

FIGURE 5a

THIS PAGE BLANK (USPTO)

6/7

Terminal appl.

H.324
H.324/M
H.324/I

A Dual-Numbering Plan

MS is NOW aware that request is for H.324 Application

HLR: this CL1 is a data service #I

(2) SETUP

(3) CALL_PROC

(5) ALERT

(7) CONNECT

(9)

V.8/V.8bis signalling detector

UMTS/GSM bearer renegotiation

(11) Modify (BC = 28.8 kbps Transparent HLC = "H.324")

(12)

MS

MSC

PSTN/C7

(1) SETUP

(4) CALL PROC

(6) ALERT

(8) CONNECT

V.8/V.8bis in-band signalling

(10)

(13)

FIGURE 5b

Terminal appl.

H.324
H.324/M

THIS PAGE BLANK (USPTO)

747

V.8	UMTS
	Bearer Capability
Call function category (Octet – "callf0") 100 PSTN Multimedia Terminal (Bits 567)	Bearer Capability Information Element Transfer mode (octet 3) 0 Circuit mode (Bit 4)
Modulation modes category (Octet – "modn0") 1 V.34 duplex availability (Bit 6)	Bearer Capability Information Element Duplex mode (octet 4) 1 Full duplex (Bit 4)
V.25ter	Bearer Capability Information Element Synchronous/Asynchronous (octet 6) 0 Synchronous (Bit 1)
Modulation control commands Modulation reporting control (+MR) +MCR: V34 +MCR: <carrier> ●R: 28800 +MRR: <rate>	Bearer Capability Information Element Fixed network user rate (octet 6d) 00100 28.8 kbps (Bits 54321)
V.8bis	Bearer Capability Information Element Acceptable channel codings (octet 6e) 1 TCH/F14.4 acceptable (Bit 7)
Standard information field - {SPar(1)} coding Standard information field – Data {NPar(2)} coding (Octet 2) 1 Rec. V.34 duplex mode (Bit 5)	Bearer Capability Information Element Acceptable channel codings (octet 6e) 1 TCH/F9.6 acceptable (Bit 5)
Standard information field - {SPar(1)} coding Standard information field – H.324 multimedia terminal {NPar(2)} coding 1 Video (Bit 1)	Bearer Capability Information Element Acceptable channel codings (octet 6e) 1 TCH/F4.8 acceptable (Bit 4)
Standard information field - {SPar(1)} coding Standard information field – H.324 multimedia terminal {NPar(2)} coding 1 Audio (Bit 2)	Bearer Capability Information Element Maximum number of traffic channels (octet 6e) 001 2 TCH (Bits 321)
	Bearer Capability Information Element Connection element (octet 6c) 00 Transparent (Bits 76)
	Bearer Capability Information Element Other modem type (octet 6d) 10 V.34 (Bits 76)
	High Layer Compatibility High Layer Compatibility Information Element High layer characteristics identification (octet 4) 1100001 PSTN Multimedia Terminal (Bits 7654321)

Figure 6

THIS PAGE BLANK (USPTO)